


Wondering what type core or reel are used with the new Imagelink catalog numbers?
Here are the new item numbers (in red) next to an image and description of the core or reel

Core, Spool, and Center-Hole Specifications

16 mm Core and Spool Specifications




Imagelink CSP 21

Type N plastic core, 3" OD, 16 mm. 1" round center hole with 10 key ways. No film slot Sp. 607.


Imagelink CSP 22

Type B plastic core, 2" OD, 16 mm. 0.320" round center hole with two keyways, for use on Unisys, NCR, IBM, and other reader sorters. Sp. 407.




Imagelink CSP 3

Type T plastic core, 2" OD, 16 mm. 1" round center hole with keyway. With film slot. Sp. 642, 642J.




Imagelink CSP 33

Type Z plastic core, 3" OD, 16 mm. 1" round center hole with keyway. With film slot. Sp. 649.



Imagelink MSP


R-186 plastic spool, flange diameter 3.600", 16 mm x 100'. Square hole with two keyways and two offset round drive holes (each hole attached to keyway). Both flanges.* 1.25" core diameter. Sp. 603, 615.



35 mm Core and Spool Specifications


Imagelink CNP 2

Type U plastic core, 2" OD, 35 mm. 1" round center hole and keyway. With film slot. Sp. 756.




Imagelink CNP3

Type K plastic core, 3" OD, 35 mm. 1" round center hole and keyway. With film slot. Sp. 684



Imagelink MNP

R-200 plastic spool, flange diameter 3.610", 35 mm x 100'. Side 1 — Square hole with three keyways and two offset drive holes. Side 2 — Square hole with two keyways and two offset drive holes.* 1.265" core diameter. Sp. 425.



105 mm Core and Spool Specifications


Imagelink CBP 21

Type UU plastic core, 2" OD, 105 mm. 1" round center hole and keyway. With film slot Sp. 827, 906.




*Center hole configuration aligned on both flanges.

**105 mm Core and Spool Specifications
(continued)**




Imagelink RMM 105

S-126 spool, flange diameter 4.375", 105 mm x 100'. Round center hole with two round drive holes. Both flanges,* 1.5" core diameter. Sp. 832.



Imagelink UCT76

PC 546 core, Inside core diameter 3". 105 mm x 500' Sp. 914



Roomlight load package The roomlight-load package is designed for loading film into a camera magazine in room light. The package is shipped in a black polyethylene bag for extra protection. Do not leave the package in room light for more than two hours after it is removed from the polyethylene bag. Sp. 827



Center Hole Specifications

Types K, T, U, Z, UU,
Modified E-

1" round center hole with keyway



R-186

0.320" square hole with two keyways and two offset round drive holes (each hole attached to keyway)




R-200 (side 1)-

0.320" square hole with three keyways and two offset drive holes (each hole attached to keyway)



R-200 (side 2)-

0.320" square hole with two keyways and two offset drive holes (each hole attached to keyway)



S-126, S-152-

0.500" round hole with two round drive holes