



Safeguard your future with archive processing today.

Committing your source document images and computer-output digital documents to microfilm assures access to important information for decades—even centuries. Proper processing is critical to protecting that access. Make certain you achieve true archival keeping with a new **Imagelink** Archive Processor, now easier to use and more ecologically friendly than ever before. It is designed for room-light operation and is quiet and compact.

START WITH AUTOMATIC THREADING. FINISH WITH ARCHIVAL QUALITY.

With the **Imagelink** Archive Processor, you don't need a film specialist to get predictable, high-quality results. It incorporates the latest in digital monitors and controls, rapid-recovery, energy-saving stand-by cycles, and an environment-friendly anti-siphon water

supply. The Archive Processor provides precisely controlled film processing with minimal operator training or experience. Simply attach film to the self-threader and insert it into the drive rollers. In less than a minute, dry, processed film begins exiting the machine. Upon completion of a roll, the Archive Processor automatically cycles into a money-saving energy-conservation mode.

TABLETOP PROCESSING THAT FITS WHERE YOU WANT IT.

Its room-light loading and tabletop size permit you to use the Archive Processor virtually anywhere. Plus, there's no mixing, no mess, and no fuss, because **Imagelink** Archive Processor chemicals come premixed in disposable plastic containers and are ready to use. You gain the added security and control of in-house processing

without the expense of a darkroom. For added convenience, parts that require periodic replacement, such as air filters, can be replaced in seconds by an operator.

The **Imagelink** Archive Processor is ruggedly built for long life and reliability and is backed by warranties and service from EPM's Worldwide Service Partner **Kodak**. When properly operated, the

Imagelink Archive Processor produces high quality microfilm meeting all applicable international standards for archival quality. Because film is available in less than minutes per roll your private records and confidential information are safeguarded within your own operations. Plus, when you use **Imagelink** Microfilm, you're protected by the **Imagelink** Disaster Recovery Program at no additional charge.

SPECIFICATIONS

Speed: 10 ft. (3 m)/min

Water Requirements:

Temperature: 96° F +/- 2° (36.5° C +/- 1.5°)

Flow rate: 0.5 gal./min (1.9 L/min)

Drain rate: 6.0 gal./min (22.7 L/min)

(Hoses for water supply and drain are included)

Electrical Requirements:

120 V AC 60 Hz (U.L. marked for U.S. and Canada)

(50 Hz available with simple field modification)

Electrical Use:

Stand-by mode: 100-200 Watts

Operational mode: 600-1,000 Watts

Warm-up mode: 1400 Watts

Chemical Capacity:

44 fl. oz. (1.3 L) each of

Imagelink Archive Processor Developer and Fixer Without replenishment will process up to 3,000 feet (900 m) of 16 mm microfilm.

With replenishment will process up to 18,000 feet (5,000 m) of 16 mm microfilm.

Physical Dimensions:

Height: 31 in. (79 cm)

36 in. (91 cm) when open

Depth: 16 in. (41 cm)

24 in (61 cm) when open

Length: 39 in. (99 cm)

Weight: 115 lb. (52 kg) empty

140 lb. (64 kg) operational

Accessories:

Imagelink Archive Processor Chemical Replenisher Unit (CAT 809 0755)

Imagelink Archive Processor Cabinet (CAT 144 4256)

Imagelink Archive Processor Thermostatic Mixing Valve (CAT 142 3698)

Imagelink Archive Processor 16 mm Self-Threader (CAT 199 0993)

Imagelink Archive Processor 16 mm Dual Strand Self-Threader (CAT 146 5194)

Imagelink Archive Processor 35 mm Self-Threader (CAT 199 1009)