

## Safeguard your future with archive processing today.

Committing your source document images and computer-output digital documents to microfilm assures access to important information for decades—even centuries. Proper processing is critical to protecting that access. Make certain you achieve true archival keeping with a new IMAGELINK Archive Processor, now easier to use and more ecologically friendly than ever before. It is designed for room-light operation and is quiet and compact.

### **START WITH AUTOMATIC THREADING. FINISH WITH ARCHIVAL QUALITY.**

With the IMAGELINK Archive Processor, you don't need a film specialist to get predictable, high-quality results. It incorporates the latest in digital monitors and controls, rapid-recovery, energy-saving stand-by cycles, and an environment-friendly anti-siphon water supply. The Archive Processor provides precisely controlled film processing with minimal operator training or experience. Simply attach film to the self-threader and insert it into the drive rollers. In less than a minute, dry, processed film begins exiting the machine. Upon completion of a roll, the Archive Processor automatically cycles into a money-saving energy-conservation mode.

### **TABLETOP PROCESSING THAT FITS WHERE YOU WANT IT.**

Its room-light loading and tabletop size permit you to use the Archive Processor virtually anywhere. Plus, there's no mixing, no mess, and no fuss, because IMAGELINK Archive Processor chemicals come premixed in disposable plastic containers and are ready to



use. You gain the added security and control of in-house processing without the expense of a darkroom. For added convenience, parts that require periodic replacement, such as air filters, can be replaced in seconds by an operator.

The IMAGELINK Archive Processor is ruggedly built for long life and reliability. When properly operated, the IMAGELINK Archive Processor produces high quality microfilm meeting all applicable international standards for archival quality. Because film is available in less than minutes per roll your private records and confidential information are safeguarded within your own operations. Plus, when you use IMAGELINK Microfilm, you're protected by the IMAGELINK Disaster Recovery Program at no additional charge.

# Specifications

---

## Speed

10 ft. (3 m)/min

## Water Requirements

Temperature: 96° F +/- 2° (36.5° C +/- 1.5°)

Flow rate: 0.5 gal./min (1.9 L/min)

Drain rate: 6.0 gal./min (22.7 L/min)

(Hoses for water supply and drain are included)

## Electrical Requirements

120 V AC 60 Hz (U.L. marked for U.S. and Canada)

(50 Hz/240V units are available )

## Electrical Use

Stand-by mode: 100-200 Watts

Operational mode: 600-1,000 Watts

Warm-up mode: 1400 Watts

## Chemical Capacity

44 fl. oz. (1.3 L) each of IMAGELINK Archive Processor Developer and Fixer without replenishment will process up to 3,000 feet (900 m) of 16 mm microfilm.

With replenishment will process up to 18,000 feet (5,000 m) of 16 mm microfilm.

## Physical Dimensions:

Height: 31 in. (79 cm)  
36 in. (91 cm) when open  
Depth: 16 in. (41 cm)  
24 in (61 cm) when open  
Length: 39 in. (99 cm)  
Weight: 115 lb. (52 kg) empty  
140 lb. (64 kg) operational

## Accessories

IMAGELINK Archive Processor Chemical Replenisher Unit (CAT 8090755)

IMAGELINK Archive Processor Cabinet (CAT 1444256)

IMAGELINK Archive Processor Thermostatic Mixing Valve (CAT142 3698)

IMAGELINK Archive Processor 16 mm Self-Threader (CAT 1990993)

IMAGELINK Archive Processor 16 mm Dual Strand Self-Threader (CAT 1465194)

IMAGELINK Archive Processor 35 mm Self-Threader (CAT 1991009)



IMAGELINK is trademark of Eastman Park Micrographics Inc.

---

866-934-4376

● info@epminc.com

● www.epminc.com